



Application of NETZSCH Products in Lithium Battery Manufacturing Industry

Pulsation-free, high precision metering, corrosion resistance

Pumps & Systems

NEMO[®] Progressing Cavity Pumps



Features of NEMO® Progressing Cavity Pumps

Flow rate is proportional to speed



High accuracy up to ± 1%



Stable conveying, no shearing to medium



Suitable for conveying medium and high viscosity materials



Lithium Battery Application of Progressing Cavity Pumps

Features

- No metal contact between wet components, so that no metal abrasive particles enter the medium.
- Rubber material has good chemical resistance.
- The pump can run in reverse under negative pressure to remove bubbles in the medium (vacuuming).
- There are a variety of metal materials to process wetted parts.

Medium characteristics

- Can transport electrode slurries, electrolyte conductive material, adhesive, UV resin, coating paste and other functional materials.
- In the production of pole pieces, various types of positive and negative electrode slurries, including solvent-based / waterbased media.
- Can transport various materials such as NMP, CNT, DIW, SBR, etc.

Reasons for choosing NEMO[®] pumps for lithium battery manufacturing

- Accurate fluid measurement and metering.
- Capable of pumping highly viscous material.
- No metal abrasive particles.
- No lubricants or oil in the pump that could contaminate the process fluid.
- Can be evacuated.
- Suitable materials (batteryresistant stator, duplex stainless steel rotor and wet parts).



Application in stirring tank workshop



Application in coating process



Application in storage reservoir discharge workshop



Design Characteristics







Hygienic quick-connections are used for inlet and outlet, which is convenient for replacement disassembling and cleaning the pump.



Stator materials available for abrasion resistance and chemical attack. PTFE and other rubber materials are resistant to corrosion by lithium slurry. Optional iFD-Stator® has an aluminum shell and allows for replacement of only the rubber portion, saving cost and maintenance time.



The rotor and wet parts are made of duplex stainless steel, which has good corrosion resistance. In special cases, the ceramic rotor can be used.



Thru bolts are constructed with a quick-change design and are manufactured out of stainless steel.

5 Base plate

The base plate can be made of stainless steel to prevent corrosion from falling medium, prevent rust, and ensure the production site is clean.



A flexible rod is used so there is no joint lubricant required thus preventing the rupture of protective joint sleeves causing lubricant to leak into the medium.

If joints are used they can also lead to the internal metal parts of the joint grinding during wear and which can get into the battery medium when the joint fails thereby affecting battery quality. The flexible rod with threaded connection is also convenient for disassembly, easy to replace the rotor head, and convenient for maintenance. 🕖 Shaft Seal

A packing gland seal is used to prevent oil from entering the contaminated medium. No lubricant is required. When the medium is suitable, a mechanical seal can also be used.



The motor case can be made of aluminum to prevent spilled or falling medium from corroding the motor and it is easy to clean. The motor can be an ordinary motor or an explosion-proof motor according to user requirements. The Mini-pump can use planetary gear reducer+ servo motor.

According to customer requirements

- Can be a directly connected structure or with bearing housing structure.
- Pump housing is polished stainless steel.

NEMO[®] Progressing Cavity Pumps Application in Lithium Battery Manufacturing Industry

Vacuum defoaming process

Slurries can be strongly suctioned even under high vacuum conditions.



Stirring process

One or more NEMO[®] pumps can transport a variety of primary raw materials to the stirring tank. After being stirred at a high speed by the stirring tank, the NEMO[®] pump will transport the media to the storage tank.



Coating process

High viscosity and high-concentration slurries can be steadily supplied without pulsation to a coater, providing a thin and even film thickness.



NEMO[®] Mini Pumps & Dispensers

NEMO[®] Mini Pump

The pump body and housing will have duplex stainless steel construction with stainless steel lantern. The pump is capable of being equipped with a servo motor and frequency converter.

Performance

- Flow rate: 0.05 gpm to 132 gpm / 0.2 l/h to 500 l/h
- Pressure : 0 to 174 psi / 0 to 12 bar

Advantages

- Small and compact
- Precise control with control system
- With sanitary quick change coupling
- For coating feed



NEMO[®] Mini Pump

NEMO[®] dispensers provide very accurate metering and extremely high repeatablity and accuracy. These dispensers are widely used in the coating process in battery manufacturing.

Performance

- Flow rate: 0.05 ml/h to 9 ml/h
- Pressure : 0 to 174 psi / 0 to 12 bar



Advantages

- Uniform coating
- No accumulation, dripping or breakpoints
- Driven by servo motor for high precision and automated control

Pumps can be controlled through centralized and simultaneous control of multiple pumps or manual / single adjustment of individual pumps. With these different methods flow changes can be achieved for battery film coating, which requires the most demanding accuracy and automation conditions.



Various Customized Designs



The NETZSCH Group is an owner-managed, international technology company with headquarters in Germany. The Business Units Analyzing & Testing, Grinding & Dispersing and Pumps & Systems represent customized solutions at the highest level. More than 3,800 employees in 36 countries and a worldwide sales and service network ensure customer proximity and competent service.

Our performance standards are high. We promise our customers Proven Excellence – exceptional performance in everything we do, proven time and again since 1873.

The NETZSCH Business Unit Pumps & Systems offers NEMO® progressing cavity pumps, TORNADO® rotary lobe pumps, NOTOS® multi screw pumps, N.Mac® twin shaft grinders, macerators, metering technology and equipment custom built for challenging solutions for different applications globally.

Proven Excellence.

NETZSCH Pumps North America, LLC 119 Pickering Way EXTON, PA 19341-1393 USA Tel.: +1 610 363 8010 Fax: +1 610 363 0971 npa@netzsch.com

NETZSCH Canada, Incorporated 500 Welham Road Barrie, ON L4N 8Z7 Canada Tel.: 705 797 8426 Fax: 705 797 8427 ntc@netzsch.com



Partner der Nachhaltigkeitsinitiative des Maschinen- und Anlagenbaus

